

The KM 632HPX with *HPXdrive Standard* for loading short logs, shrubbery, branches etc. A non-return valve secures constant pressure even in case of unexpected pressure drop. The revolutionary *HPXdrive* technology guarantees a reliable and low-maintenance attachment.

- ▷ **Reliability** of the HPXdrive! The movement of the arms of the grapple is generated by two hollow shafts, which run opposed and have a helix thread, hydraulically driven by a single piston. No more hydraulic cylinder.
- ▷ **Longer life cycle** up to 50%! The drive unit runs in a permanent oil bath – no lubrication service is necessary. The compact design makes the HPXdrive resistant to dirt and debris.
- ▷ **Versatility** with different types of shells that can easily be refitted onto the drive unit.
- ▷ **Profitability** through low maintenance costs and longer life cycle.
- ▷ **Precise handling** with the gear-type KINSHOFER rotator and shells synchronised by the single piston turning both shafts.
- ▷ **Rotator with shaft** is available as an alternative, in case a quick change to a non-rotating hook is favoured.
- ▷ **Constant closing force** (3,960 lbf at 3,750 psi operating pressure) for the entire opening and closing process.



Package timber grapple KM 632HPX with KINSHOFER flange rotator								
Type	Capacity	Width B	Height	Log-Ø min.	Opening max.	Self weight	Closing force	Load capacity
	(cords)	(in)	(in)	(in)	(in)	(lbs)	(lbf)	(lbs)
KM 632HPX-0,16 c	0.11	32	39	6.7	48	517	3,960	2,200

Package consists of: timber grapple, rotator KM 04 F140-30V, upper suspension KM 501 4500, pressure relief valve, non-return valve

Please note:

- KM 632HPX is also available with a shaft rotator and quick change system KM 505
- for heavy duty tasks we recommend to use quick change KM 505 HD with rotator KM 04 S68-30US

Package timber grapple KM 632HPX/502 with KINSHOFER rotator with shaft and reduction link								
Type	Capacity	Width B	Height	Log-Ø min.	Opening max.	Self weight	Closing force	Load capacity
	(cords)	(in)	(in)	(in)	(in)	(lbs)	(lbf)	(lbs)
KM 632HPX-0,16/502 c	0.11	16	41.5	6.7	48	528	3,960	2,200

Package consists of: timber grapple, rotator KM 04 S, reduction link KM 502 4500, short connecting hoses KM 203 01, upper suspension KM 501 4500, pressure relief valve, non-return valve

Accessories	
Type	Description
KM 204 01	mobile part of hydraulic quick coupling for hose (Ø 0.4 in, 2 pieces)
KM 204 02	fixed part of hydraulic quick coupling for rotator (Ø 0.4 in, 2 pieces)

Requirements of truck crane

Operating pressure at oil flow:

3,750 psi at max. 20 GPM

2,900 - 5,350 psi at max. 10.5 GPM

Technical drawings

